

TS2

SERIES

-

[Placeholder]

-

[Placeholder]

-

[Placeholder]

-

[Placeholder]

-

[Placeholder]

-

[Placeholder]

LIMITER OPTION:

S SQUARE (□)
 R ROUND (O)
 Y Y LIMITER (I)
 G GUIDED FEEL (□ /+)

OUTPUT OPTION:

1 0V-5V
 2 0.5V to 4.5V
 3 0.25V to 4.75V
 4 1V to 4V

ACTUATOR COLOR:

BK BLACK
 GY GREY

ACTUATOR OPTION:


1 CASTLE CAP, ELASTOMER
 2 ROUND, CONVEX, ELASTOMER
 3 SINGLE AXIS Y, ELASTOMER
 4 ROUND, CONCAVE, ELASTOMER
 5 CONVEX, NARROW, ELASTOMER
 H6 HARD PLASTIC CASTLE

MOUNTING OPTION:

T 1/2"-20 THREADED HOUSING

TERMINATION:

B .049" (1.25mm) JST Connertor without mating wire harness
 C .049" (1.25mm) JST Connector*
 W 24AWG Pigtail, 14" Length
 Z 28AWG Pigtail, 14" Length



*Note: Connectorized Version (Termination Option "C") Supplied With JST Connector & 14" (28AWG) Mating Wire Harness